

Crown Bevcan, Europe &amp; Middle East

www.crowncork.com

 Status: **Approved**

 Issue Date: **26 October 2015**

 Version Number: **6**

 Authorised By: **Matthew Wheatley**

Nominal Fill Volume :	<b>250ml</b>
Container Brimful Capacity :	<b>279ml +/- 1.8</b>
Individual Axial Load :	<b>800N min.</b>
Minimum Dome Reversal Pressure :	<b>6.2bar</b>
Internal Lacquer Specification :	<b>Water Based Epoxy</b>
External Base Protection :	<b>Single Rim Coat</b>
Nominal Bright Container Weight :	<b>8.5g</b>



## Can Specification

Entity Code	Entity Description	Value	Tolerance
B	Inside Neck Diameter	50.00 mm	±0.30
D	Outside Can Diameter	53.30 mm	max.
E	Flange Width	2.10 mm	±0.25
Et	Flange Thickness	0.160 mm	nom.
F	Flange Diameter	54.70 mm	max.
FE	Dome Depth	9.53 mm	
G	Nesting Depth	2.40 mm	nom.
H	Factory Finished Can Height	134.00 mm	±0.30
HS	Headspace	14.10 mm	nom.
J	Neck Seaming Clearance	3.0 mm	min.
kd	Stand Diameter	46.20 mm	
N	Neck Length	9.80 mm	
rb	Flange Radius	2.03 mm	nom.
XB	Flange Angle	7.5 deg max.	

