

Crown Bevcan, Europe & Middle East

www.crowncork.com

Status: **Approved**

Issue Date: **24 March 2017**

Version Number: **11**

Authorised By: **Florent Gourven**

Nominal Fill Volume :	150ml
Container Brimful Capacity :	181ml +/- 1.8
Individual Axial Load :	800N min.
Minimum Dome Reversal Pressure :	6.2bar
Internal Lacquer Specification :	Water Based Epoxy
External Base Protection :	Single Rim Coat
Nominal Bright Container Weight :	6.5g



Can Specification

Entity Code	Entity Description	Value	Tolerance
B	Inside Neck Diameter	50.00 mm	±.30
D	Outside Can Diameter	53.30 mm	max.
E	Flange Width	2.10 mm	±.25
Et	Flange Thickness	.157 mm	nom.
F	Flange Diameter	54.70 mm	max.
FE	Dome Depth	9.53 mm	
G	Nesting Depth	2.40 mm	nom.
H	Open Can Height	88.40 mm	±.30
HS	Freeboard Depth	14.10 mm	nom.
J	Neck Seaming Clearance	3.0 mm	min.
kd	Stand Diameter	46.20 mm	
N	Neck Length	9.80 mm	
rb	Flange Radius	2.03 mm	nom.
XB	Flange Angle	7.5° max.	

